



# Technical Datasheet

Product group:  
SPC 3,2mm

## Dimensions/Packaging/Product Information:

Lenght mm		1220	Items: 4052-0201; 4118-0101; 4119-0101
Width mm		182	Items: 4052-0201; 4118-0101; 4119-0101
Strength mm		3,2	Items: 4052-0201; 4118-0101; 4119-0101
Base unit		m <sup>2</sup>	Items: 4052-0201; 4118-0101; 4119-0101
Base unit/Pal		136,777	Items: 4052-0201; 4118-0101; 4119-0101
Base unit/Packing unit		3,109	Items: 4052-0201; 4118-0101; 4119-0101
Bevel		no groove	Items: 4052-0201; 4118-0101; 4119-0101
Surface structure		Textured embossing	Items: 4052-0201; 4118-0101; 4119-0101
Utilisation class		31	Items: 4052-0201; 4118-0101; 4119-0101
Wear layer		0,2 mm	Items: 4052-0201; 4118-0101; 4119-0101
Clicksystem		Loc-Click - uniclic	Items: 4052-0201; 4118-0101; 4119-0101
Guarantee private		2 Jahre private warranty	Items: 4052-0201; 4118-0101; 4119-0101
Guarantee commercial		2 Jahre commercial warranty	Items: 4052-0201; 4118-0101; 4119-0101
Pal/Truck		26	Items: 4052-0201; 4118-0101; 4119-0101
Pal/CTN		29	Items: 4052-0201; 4118-0101; 4119-0101

## Tests performed / Technical data

Category	Test standard	Result	Items:
Fire behavior	EN 13501-1	Bfl-s1	4052-0201; 4118-0101; 4119-0101
Colour Fastness To Light	ISO 105-B02	Level 6	4052-0201; 4118-0101; 4119-0101
Electrical behaviour	EN 14041	≤ 2kV	4052-0201; 4118-0101; 4119-0101
Resistance to staining	EN 438-2	Grp. 1, 2, 3: Grad(e) 5	4052-0201; 4118-0101; 4119-0101
Stubbed cigarettes test	EN 1399	OK	4052-0201; 4118-0101; 4119-0101
Effect of a castor chair	EN 4918	OK	4052-0201; 4118-0101; 4119-0101
Dimensional stability	ISO 23999	≤ 0,06%	4052-0201; 4118-0101; 4119-0101
Squareness	EN 16511	OK	4052-0201; 4118-0101; 4119-0101
Straightness	EN 16511	OK	4052-0201; 4118-0101; 4119-0101
Flatness	EN 16511	OK	4052-0201; 4118-0101; 4119-0101
Joint opening	EN 16511	OK	4052-0201; 4118-0101; 4119-0101
Height difference of joints	EN 16511	OK	4052-0201; 4118-0101; 4119-0101
Residual indentation	ISO 24343-1	≤ 0,01mm	4052-0201; 4118-0101; 4119-0101
Slip resistance	EN 13893	DS	4052-0201; 4118-0101; 4119-0101
Slip resistance (oil-wet ramp test)	DIN 51130	R10	4052-0201; 4118-0101; 4119-0101
Thermal conductivity	EN 12667	0,1[W/(m·K)]	4052-0201; 4118-0101; 4119-0101

Technical Datasheet - SPC 3,2mm



Thermal resistance	EN 12667	0,032[(m <sup>2</sup> ·K)/W]	Items: 4052-0201; 4118-0101; 4119-0101
Underfloor heating		max. 28°C	Items: 4052-0201; 4118-0101; 4119-0101
Content of Pentachlorophenol (PCP)	EN 12673	< 5ppm	Items: 4052-0201; 4118-0101; 4119-0101
Formaldehyde class	EN 717-1	E1	Items: 4052-0201; 4118-0101; 4119-0101
Wear resistance	EN 13329 // EN 15468	≥ 7.000	Items: 4052-0201; 4118-0101; 4119-0101
Scratch resistance	EN 16094	MSR-A1, MSR-B1	Items: 4052-0201; 4118-0101; 4119-0101
Swelling	ISO 24336	< 0,1%	Items: 4052-0201; 4118-0101; 4119-0101
Locking Strength	ISO 24334	l ≥ 4,6kN/m, w ≥ 4,4kN/m	Items: 4052-0201; 4118-0101; 4119-0101
french VOC		A+	Items: 4052-0201; 4118-0101; 4119-0101
REACH		OK	Items: 4052-0201; 4118-0101; 4119-0101
TÜV profi cert		OK	Items: 4052-0201; 4118-0101; 4119-0101

We would like to point out that Koczwarra Vertriebs-GmbH complies with all applicable regulations for product launches in the EU and other served markets, in addition to the certificates and regulations listed here.  
The information provided serves as a basis for understanding and overview and is not exhaustive.

Need further information? Get in contact with us: [info@koczwarra-vertrieb.de](mailto:info@koczwarra-vertrieb.de)



Koczwarra Vertriebs-GmbH (2026)  
Scheuten-Solar-Str. 2  
D-45881 Gelsenkirchen  
Tel.: +49 209 / 59034-0  
[info@koczwarra-vertrieb.de](mailto:info@koczwarra-vertrieb.de)  
[www.koczwarra-vertrieb.de](http://www.koczwarra-vertrieb.de)

Stand: 25.03.2026