

## No: FOF M8R B700 - 15BM04

1. Unique identification code of the product type: **FOF M8R B700**
2. Intended use: Roof windows for use in non-heated, uninhabited spaces in buildings
3. Manufacturer: Altaterra Kft., Hungary, 9431 Fertőd, Malom köz 1. [www.altaterra.eu](http://www.altaterra.eu)
5. Systems of assessment and verification of constancy of performance (AVCP): System 3
- 6a. Harmonised standard: EN 14351-1:2006+A2:2016 Notified body/ies: 0757, 1415
7. Declared performance:

Essential Characteristics	Performance	§	NB*
Resistance to wind load	npd**	4.2	
Resistance to snow load	4H-16-4***	4.3	
Reaction to fire	C s1,d0	4.4.1	1415
External fire performance	npd	4.4.2	
Watertightness	E1200	4.5	0757
Impact resistance	npd	4.7	
Load-bearing capacity of safety devices	npd	4.8	
Acoustic performance $R_w$	32 (-1;-5) (dB)	4.11	14351-1
Thermal transmittance ( $U_w$ )	1,5 (W/m <sup>2</sup> K)	4.12	0757
Solar factor (g)	0,6	4.13	0757
Light transmittance ( $T_w$ )	0,77	4.13	0757
Air permeability	4	4.14	0757

npd: No Performance Determined

\* Notified body/ies: <http://ec.europa.eu/growth/tools-databases/nando/>

\*\* For window width > 1140 mm or window height > 1398 mm: NPD

\*\*\* Layers from outside to inside. H: toughened, HS: heat-strengthened

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Krzysztof Dudek  
Chief Executive Officer



Altaterra Kft.  
Malom köz 1.  
HU-9431 Fertőd  
Hungary  
[www.altaterra.eu](http://www.altaterra.eu)



**FOF M8R B700 - 15BM04**  
**Roof windows for use in non-heated, uninhabited**  
**spaces in buildings**

**Harmonised**  
**standard EN**  
**14351-1:2006**  
**+A2:2016**

<b>Essential Characteristics</b>	<b>Performance</b>	<b>§</b>	<b>NB*</b>
Resistance to wind load	npd**	4.2	
Resistance to snow load	4H-16-4***	4.3	
Reaction to fire	C s1,d0	4.4.1	1415
External fire performance	npd	4.4.2	
Watertightness	E1200	4.5	0757
Impact resistance	npd	4.7	
Load-bearing capacity of safety devices	npd	4.8	
Acoustic performance $R_w$	32 (-1;-5) (dB)	4.11	14351-1
Thermal transmittance ( $U_w$ )	1,5 ( $W/m^2K$ )	4.12	0757
Solar factor (g)	0,6	4.13	0757
Light transmittance ( $T_w$ )	0,77	4.13	0757
Air permeability	4	4.14	0757

npd: No Performance Determined

\* Notified body/ies: <http://ec.europa.eu/growth/tools-databases/nando/>

\*\* For window width > 1140 mm or window height > 1398 mm: NPD

\*\*\* Layers from outside to inside. H: toughened, HS: heat-strengthened