

**DECLARATION OF PERFORMANCE NO 01CE/Bla/CSE/04**

1. The unique identification code of the product type: **01/Bla/UGL/CSE**
2. Intended use or use:  
**Dry-pressed ceramic tiles with low water absorption  $E \leq 0.5\%$ ; Annex G; Bla group, unglazed (UGL) Gres Porcellanato; for interior and exterior walls and floors of buildings - as described on the packaging.**
3. Manufacturer: **CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce**
4. System(s) of assessment and verification of constancy of performance: **SYSTEM 4**
5. Harmonised standard: **EN 14411:2012**
6. Declared performance:


Essential characteristics	Performance (level and/or class)	Harmonised technical specification	
Reaction-to-fire performance	A1 <sub>FL</sub>	Classified Without Testing (CWT)	
<b>Release of dangerous substances:</b>			
- Cadmium	Max 0,07mg/mm <sup>2</sup>	EN 14411:2012	
- Lead	Max 0,8mg/mm <sup>2</sup>		
<b>Breaking strength:</b>			
- thickness $\geq 7,5$ mm	$\geq 1300$ N		
- thickness $< 7,5$ mm	$\geq 700$ N		
<b>Bond strength/adhesion [N/mm<sup>2</sup>]:</b>			
- cementitious adhesives	NPD - No Performance Determined		
- dispersion adhesives			
- reaction resin adhesives			
- mortar			
Slippage according to DIN 51130	According to the packaging		
Thermal shock resistance	Meets		
<b>Durability for:</b>			
- internal use:	Meets		
- external use: resistance to freeze-thaw cycles	Meets		
Tactility	NPD - No Performance Determined		

A copy of the Declaration of Performance is available on the website: [www.cersanit.com](http://www.cersanit.com)

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

Kielce, 01.62017  
(place and date of issue)

QUALITY SYSTEM MANAGER  
  
.....  
(signature)