

Declaration of Performance



N° DoP: 06-002 2016-12-12

Unique identification code of the product-type	Corrugated bitumen sheet - Category S Onduline® BASE, Onduline® STANDARD, Onduline® EASYLINE, Onduline® EASYFIX, Onduline® EASYFIX COMPACT, Onduline® EASYSTYLE, Onduline® DURO SX
Intended use/es	Discontinuously laid pitched roof coverings for buildings
Manufacturer	Onduline SA 5-7 rue Frédéric Clavel FR-92150 Suresnes
System/s of AVCP Harmonised standard Notified body/ies	System 3 (reaction to fire) System 4 EN 534:2006 +A1:2010 1488 - Instytut Techniki Budowlanej - Poland

Declared performances

Essential characteristics	Unit	Performance	Harmonised standard
Bending under downward load	N/m ²	> 700	EN 534:2006 +A1:2010
Impact strength	mm	250	
Tearing strength	N	≥ 150	
Tearing strength after freeze/thaw ageing	N	≥ 150	
Water permeability	Pass/Fail	Pass	
Water permeability after freeze/thaw ageing	Pass/Fail	Pass	
Thermal coefficient	10 ⁻⁶ 1/K	< 100	
Reaction to fire	Class	E	
External fire performance	Class	Froof	
Dangerous substances	-	NPD*	

*NPD: No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number: v04

Signed for and on behalf of the manufacturer by

TAWILE Nay
Managing Director Europe
Paris, 25.01.2024