

Declaration of Performance

N° DoP: 2024-002 SA11



Unique identification code of the product-type:

BARDOLINE® DETAIL STRIP

Intended use/es:

Roof Waterproofing (Multilayer systems: Exposed layer)

Manufacturer:

Onduline
5-7 rue Frédéric Clavel
92150 Suresnes - France

System/s of AVCP:

System 2+

Harmonised standard :

EN 13707:2004 + A2:2009

Notified body/ies:

1415 - EMI Építésügyi Minőségellenőrző Innovációs Nonprofit Kft.

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
External Fire Resistance (Class)	Froof	-	-	EN 13501-5
Reaction to Fire (Class)	F	-	-	EN 13501-1
Watertightness (Method A) (kPa)	≥10	-	-	EN 1928
Tensile Resistance MD/CMD (N/5cm)	300 / 200	±20%		EN 12311-1
Elongation MD/CMD (%)	2 / 2	±1		EN 12311-1
Resistance to Static Loading (Method A) (Kg)	≥10	-	-	EN 12730
Resistance to Impact (Method A) (mm)	≥700	-	-	EN 12691
Resistance to Tearing (Nail Method) MD/CMD (N)	70 / 70	-30%	-30%	EN 12310-1
Shear Resistance of Joints (N/5cm)	NPD	-	-	EN 12317-1
Flexibility at Low Temperatures (°C)	≤0	-	-	EN 1109
Flow Resistance at High Temperatures (°C)	≥110	-	-	EN 1110
Durability: Flow Resistance at High Temperatures, after Thermal Aging (°C)	≥100	-	-	EN 1296 / EN 1110
Artificial Aging by Long Term Exposition to a Combination of UV Radiations, High Temperature and Water (Visual)	NPD	-	-	EN 1297 / EN 18501
Dangerous substances	NPD			-

NPD* : No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v02

Signed for and on behalf of the manufacturer by:

Nay TAWILE
Suresnes, 06/11/2024