Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or | trade mark: | STEMNING |
|--------------------|-------------|----------|
|--------------------|-------------|----------|

Supplier's address: Jem & Fix, Skomagervej 12, 7100 Vejle, DK

Model identifier: 9060573

| Type of light source: | Type | of light | source: |
|-----------------------|------|----------|---------|
|-----------------------|------|----------|---------|

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|----------------|---------------------------------|-------|
| Light source cap-type | other elec- | | |
| (or other electric interface) | tric interface | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |
| Product parameters | | | |
| Parameter | Value | Parameter | Value |

| Product parameters | | | | |
|---|--|-------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| | | General product p | parameters: | |
| <u> </u> | nption in on- 00 h), rounded st integer | 3 | Energy efficiency class | G |
| dicating if it refe a sphere (360º) | s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º) | 100 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 2,2 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| (P _{net}) for CLS, 6 | andby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 88 |
| Outer dimen- | Height | 4 900 | Spectral power dis- | See image |
| sions without | Width | 30 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 8 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | |
|--|------|------------------------------|-------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordi- | 0,463 |
| | | nates (x and y) | 0,420 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 |
| the lumen maintenance factor | 0,90 | | |

(a)'-': not applicable; (b)'-': not applicable;

Spectrum

