## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: STEMNING

Supplier's address: Jem & Fix, Skomagervej 12, 7100 Vejle, DK

## Model identifier: 9060581

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	other elec-				
(or other electric interface)	tric interface				
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter		Value	Parameter	Value			
General product parameters:							
Energy consur mode (kWh/10 up to the neares	00 h), rounded	6	Energy efficiency class	G			
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone nrrow cone (90º)	490 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	2 500			
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	6,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00			
(P <sub>net</sub> ) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen- sions without separate con- trol gear, light- ing control	Height Width Depth	19 900 30 8	Spectral power dis- tribution in the range 250 nm to 800 nm, at full-load	See image in last page			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,485		
		nates (x and y)	0,427		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,90		
the lumen maintenance factor	0,90				

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

