## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Jem & Fix, Skomagervej 12, 7100 Vejle, DK

Model identifier: 9060600

Type	of	light	source:
-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		0	

Type of light source.					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	other elec-				
(or other electric interface)	tric interface				
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded	4	Energy efficiency class	G		

Lluminous flux (duso) in	220 in	Corrolated	colour	2 500
the nearest integer				
(kwn/1000 n), rounded		class		

up to the nearest integer			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	230 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500
On-mode power (P <sub>on</sub> ), expressed in W	3,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec-	0,00

			rounded to the sec- ond decimal	
Networked st	tandby power	-	Colour rendering in-	89
(P <sub>net</sub> ) for CLS, 6	expressed in W		dex, rounded to the	
and rounded to	the second dec-		nearest integer, or	
imal			the range of CRI-val-	
			ues that can be set	
Outer dimen-	Height	1 500	Spectral power dis-	See image
sions without	\\/;d+b	990	tribution in the	in last nage

Outer dimen-	Height	1 500	Spectral power dis-	See image
sions without		880	tribution in the	in last page
separate con-	Denth	880	range 250 nm to 800	
trol gear, light-	2000.	000	nm, at full-load	
ing control				

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,485	
		nates (x and y)	0,427	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,90			

(a)'-': not applicable; (b)'-': not applicable;

## **Spectrum**

