## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Jem & Fix, Skomagervej 12, 7100 Vejle, DK

Model identifier: 9060604

Type	of	light	source:
-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		0	

71 6					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	other elec-				
(or other electric interface)	tric interface				
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					
Parameter	Value	Parameter	Value		

Troduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
<u> </u>	mption in on- 00 h), rounded st integer	5	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		430 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P <sub>on</sub> ), expressed in W		4,8	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	88		
Outer dimen-	Height	30 000	Spectral power dis-	See image		
sions without	Width	27	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	5	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,437		
		nates (x and y)	0,405		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,90		
the lumen maintenance factor	0,90				

(a)'-': not applicable; (b)'-': not applicable;

## **Spectrum**

