## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Jem & Fix, Skomagervej 12, 7100 Vejle, DK

Model identifier: 9060606

_		•	••			
11/	no.	Λt	$\mathbf{H}\boldsymbol{\alpha}$	nt	$c \cap$	urca.
1 V	νC	VI.	IIE	116	30	urce:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	other elec-					
(or other electric interface)	tric interface					
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Due do et a care estare						

## **Product parameters**

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	E		
dicating if it refe a sphere (360º)	s flux (фuse), iners to the flux in , in a wide cone arrow cone (90º)	730 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P <sub>on</sub> ), expressed in W		5,7	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	86		
Outer dimen-	Height	29 850	Spectral power dis-	See image		
sions without	Width	700	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	5	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,437			
		nates (x and y)	0,405			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,90					

(a)'-': not applicable; (b)'-': not applicable;

## **Spectrum**

