

SAFETY DATA SHEET



Hey'di Bolt Fast comp. B (resin)



The safety data sheet is in accordance with Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 1: Identification of the substance / mixture and of the company / undertaking

Date issued	14.06.2012
Revision date	18.09.2019

1.1. Product identifier

Product name	Hey'di Bolt Fast comp. B (resin)
Article no.	650-2
GTIN No.	7054150006507
Information on the packaging	Type of packaging: Box Size of packaging: 1,5 kg Material of packaging: Metal Child-resistant packaging: No Tactile warnings: No Description of the packaging: Set with comp. A, B and C.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Function	Description: Strong anchoring. Epoxy based casting compound and adhesive.
Use categories nordic (UCN).	L1060
Use of the substance / mixture	Hey'di Bolt Fast is a two-component, shrink-free, fast-curing casting compound used for anchoring metal objects in concrete and rock, where there are high demands on strength and adhesion, e.g. bolts, pillars, handrails, reinforcements, etc.
Relevant identified uses	SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys) SU21 Consumer uses: Private households (= general public = consumers) PC1 Adhesives, Sealants PROC5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC19 Manual activities involving hand contact. ERC2 Formulation of preparations ERC5 Industrial use resulting in inclusion into or onto a matrix ERC6A Industrial use resulting in manufacture of another substance (use of intermediates)

	ERC8F Wide dispersive outdoor use resulting in inclusion into or onto a matrix
Uses advised against	Minimum application temperature is +5 °C.
Standard industrial classification (NACE)	23.650
Industrial use	Yes
Professional use	Yes
Consumer use	Yes

1.3. Details of the supplier of the safety data sheet

Downstream user

Company name	HeyDi AS
Office address	Tretjerdalsvegen 68
Postcode	N-2016
City	Frogner
Country	Norway
Telephone number	+47 63868800
Email	heydi@heydi.no
Website	www.heydi.no
Enterprise No.	979657919
Contact person	Alan Ulstad

1.4. Emergency telephone number

Emergency telephone	Telephone number: +47 22 59 13 00 Description: The National Poisons Information Centre
---------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP / GHS]	Skin Sens. 1; H317 Aquatic Chronic 2; H411 Eye Irrit. 2; H319 Skin Irrit. 2; H315
Substance / mixture hazardous properties	Contains epoxy constituents. May produce an allergic reaction.

2.2. Label elements

Hazard pictograms (CLP)



Composition on the label	Reaction product: bisphenol-A- (epichlorohydrin) epoxy resin (number average molecular weight <= 700) 50 - 70 %, Bisphenol-F Epoxy resin 20 - 40 %, Oxirane, mono[(C12- 14- alkyloxy) methyl]derivs
Signal word	Warning
Hazard statements	H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects. H319 Causes serious eye irritation. H315 Causes skin irritation. EUH 205 Contains epoxy constituents. May produce an allergic reaction.
Precautionary statements	P102 Keep out of reach of children. P280 Wear protective gloves / protective clothing / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice / attention. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or rash occurs: Get medical advice / attention. P273 Avoid release to the environment. P501 Dispose of contents / container to an authorized waste operator according to local regulations.
Tactile warnings	No
Child-protection	No

2.3. Other hazards

PBT / vPvB	This product does not contain any PBT or vPvB substances.
Hazard description, general	Contains epoxy compounds. May cause an allergic reaction. When mixing two components, the safety data sheets for both components must be consulted.
Health effect	Vapours/aerosol spray may irritate the respiratory system. Contains epoxy constituents. May produce an allergic reaction. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. See section 11 for additional information on health hazards.
Environmental effects	Toxic to aquatic life with long lasting effects.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Substance	Identification	Classification	Contents	Notes
Reaction product:	CAS No.: 25068-38-6	Skin Irrit. 2; H315	50 - 70 %	1
bisphenol-A- (epichlorohydrin) epoxy resin (number average molecular weight <= 700)	EC No.: 500-033-5	Eye Irrit. 2; H319		
	Index No.: 603-074-00-8	Skin Sens. 1; H317		
	REACH Reg. No.: 01-2119456619-26	Aquatic Chronic 2; H411		
Bisphenol-F Epoxy resin	CAS No.: 28064-14-4	Skin Irrit. 2; H315	20 - 40 %	1
	EC No.: 608-164-0	Skin Sens. 1; H317		
	REACH Reg. No.: 01-2119454392-40-xxxx	Eye Irrit. 2; H319		
		Aquatic Chronic 2; H411		
Oxirane, mono[(C12- 14- alkyloxy) methyl] derivs	CAS No.: 68609-97-2	Skin Irrit. 2; H315	5 - 15 %	1
	EC No.: 271-846-8	Skin Sens. 1; H317		

Index No.: 603-103-00-4

REACH Reg. No.:

01-2119485289-22

2

2

¹Substance classified with a health or environmental hazard²Substance with a workplace exposure limit

Description of the mixture	Modified epoxy resin.
Substance comments	The full text for all hazard statements is displayed in section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General	Remove affected person from source of contamination. Frisk luft. Contact physician if discomfort continues.
Inhalation	Move the exposed person to fresh air at once. Ensure free airways, seek medical attention if irritation persists.
Skin contact	Remove contaminated clothing and launder thoroughly before re-use. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Do not rub eye. Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.
Ingestion	Induce vomiting, if person is conscious. Rinse mouth immediately and then drink plenty of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Acute symptoms and effects	Irritating to eyes and skin May cause sensitization by skin contact.
Delayed symptoms and effects	May cause hypersensitivity after skin contact. Symptoms include redness, swelling, blisters and ulceration and are usually developed slowly.

4.3. Indication of any immediate medical attention and special treatment needed

Medical treatment	Symptomatic treatment.
Medical monitoring for delayed effects	Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray, foam, dry powder or carbon dioxide.
Improper extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards	The product is decomposed by fire or heating to high temperatures, and flammable and toxic gases can be formed.
Hazardous combustion products	Carbon dioxide (CO ₂). Carbon monoxide (CO). Nitrous gases (NO _x).

5.3. Advice for firefighters

Personal protective equipment	Use fresh air equipment when the product is involved in fire.
Fire fighting procedures	Containers close to fire should be removed or cooled with water. Do not scatter spilled material with more water than needed to fight the fire.
Special protective equipment for firefighters	Use a self-contained fresh air breathing apparatus and chemical protective clothing.
Other information	This Product is toxic to aquatic life with long lasting effects. Residues from the fire and contaminated extinguishing water should be disposed of in accordance with local regulations. Residues from the fire and contaminated extinguishing water should be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Use personal protective equipment as specified in section 8.
Personal protection measures	Do not breathe vapour. Avoid contact with skin and eyes. Use appropriate protective equipment.
Emergency procedures	Stop leak if safe to do so.
For emergency responders	Use the specified safety equipment. See section 8.

6.2. Environmental precautions

Environmental precautionary measures	Do not discharge into drains, water courses or onto the ground.
--------------------------------------	---

6.3. Methods and material for containment and cleaning up

Containment	Store in a closed container. Store in a well-ventilated place.
Clean up	Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol/Hazard pictograms. Product residues should be delivered to a hazardous waste disposal site.

6.4. Reference to other sections

Other instructions	See section 1 for emergency contact information. See section 8 for information on appropriate personal equipment. See section 13 for waste disposal.
--------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling	Provide good ventilation. Avoid contact with eyes and prolonged skin contact.
----------	---

Persons with impaired lung functions should not handle this preparation. Persons susceptible to allergic reactions should not handle this product. Do not wipe your hands with rags. Instead, use paper towel or similar. When using do not eat, drink or smoke. Use appropriate protective equipment as described in section 8 when handling open containers.

When mixing two components, the safety data sheets for both components must be consulted. For more information about mixing ratio, refer to the technical data sheet.

Protective safety measures

Safety measures to prevent fire	Keep away from heat / sparks / open flames / hot surfaces. — No smoking. Store in a well-ventilated place. Keep container tightly closed.
Preventitive measures to protect the environment	Do not discharge into drains, soil or streams.
Advice on general occupational hygiene	Provide easy access to water supply or an emergency shower. First-aid equipment, including eye wash bottle, must be available at the work site. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage	Keep out of reach of children. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feeding stuffs.
Conditions to avoid	Do not store near heat sources or exposed to high temperatures.

Conditions for safe storage

Technical measures and storage conditions	Keep flammable liquids away from flammable gas and highly flammable goods.
Packaging compatibilities	Store in tightly sealed original packaging.
Requirements for storage rooms and vessels	Keep above the chemical's freezing point to avoid rupturing the container.
Advice on storage compatibility	No specific advice on storage is indicated.
Additional information on storage conditions	Store in a well-ventilated place. Keep container tightly closed.
Storage stability	Best performance within 2 years of production date.

7.3. Specific end use(s)

Recommendations	Read the description in the technical datasheet about surface treatment before use.
Specific use(s)	A two-component, shrink-free, fast-curing casting material used for anchoring metal objects in concrete and rock, where there are high demands on strength and adhesion, e.g. bolts, pillars, handrails, reinforcements, etc.

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Substance	Identification	Exposure limits	TWA Year
Bisphenol-F Epoxy resin	CAS No.: 28064-14-4		
Oxirane, mono[(C12- 14-alkyloxy) methyl] derivs	CAS No.: 68609-97-2		
Oil vapour		Limit value (8 h) : 50 mg/m ³	
Oil mist (mineral oil particle)		Limit value (8 h) : 1 mg/m ³	

DNEL / PNEC

Substance	Bisphenol-F Epoxy resin
DNEL	Group: Industrial Route of exposure: Acute dermal (local) Value: 104,15 mg/kg bw/day Group: Industrial Route of exposure: Acute inhalation (local) Value: 29,39 mg/m ³
Substance	Oxirane, mono[(C12- 14-alkyloxy) methyl]derivs
DNEL	Group: Industrial Route of exposure: Acute dermal (local) Value: 3,9 mg/kg bw/day Group: Industrial Route of exposure: Acute inhalation (local) Value: 13,8 mg/m ³

8.2. Exposure controls

Safety signs



Precautionary measures to prevent exposure

Appropriate engineering controls	Observe occupational exposure limits and minimize the risk of inhalation of vapours.
Instruction on measures to prevent exposure	The usual precautions for handling chemicals should be followed. Wear proper protective equipment.
Organisational measures to prevent exposure	All work must be planned to ensure minimal inhalation of vapours and contact with skin.
Technical measures to prevent exposure	Provide adequate general and local exhaust ventilation.

Eye / face protection

Suitable eye protection	Wear tight-fitting goggles or face shield.
Eye protection equipment	Description: Wear tight-fitting goggles or face shield. Reference to relevant standard: EN 166

Hand protection

Suitable gloves type	Neoprene, nitrile, polyethylene or PVC.
Breakthrough time	Value: > 120 minute(s)
Hand protection equipment	Description: Neoprene, nitrile, polyethylene or PVC. Reference to relevant standard: EN 374

Skin protection

Protective clothing necessary properties	Wear appropriate clothing to prevent reasonably probable skin contact.
Recommended protective clothing	Description: Wear appropriate clothing to prevent any possibility of skin contact. Reference to relevant standard: ISO 13688
Skin protection remark	Contaminated protective clothing should be washed before reuse.

Respiratory protection

Respiratory protection necessary at	In case of inadequate ventilation use suitable respirator.
Recommended type of equipment	Chemical respirator with organic vapour cartridge.
Recommended respiratory protection	Mask type: Use respiratory equipment with particle filter, type P3. Reference to relevant standard: EN 136/140/145

Hygiene / environmental

Specific hygiene measures	Wash promptly if skin becomes wet or contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. Contaminated tools should be washed before reuse.
---------------------------	--

Appropriate environmental exposure control

Environmental exposure controls	The product must not be discharged directly into drains or waterways without treatment.
---------------------------------	---

Exposure controls

Safety measures for consumer use of the chemical	Use the specified safety equipment. See section 8.
Exposure controls and personal protection, additional information	All protection should be CE marked.
Exposure controls, comments	Wash hands before breaks, lavatory and before leaving the work site.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Clear
Odour	Characteristic.
Odour limit	Comments: Not known.
pH	Status: In delivery state

	Comments: Not relevant.
Boiling point / boiling range	Comments: Not known.
Evaporation rate	Comments: Not known.
Explosion limit	Comments: Not known.
Density	Value: ~ 910 kg/m ³
Solubility	Comments: Not soluble in water.
Partition coefficient: n-octanol/ water	Comments: Not known.
Auto-ignition temperature	Comments: Not known.
Decomposition temperature	Comments: Not known.
Explosive properties	No explosive properties.
Oxidising properties	No oxidizing properties.

9.2. Other information

Physical hazards

Conductivity	Comments: Not relevant.
Air reactive	Not known.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Protect from sunlight. Store in a well-ventilated place.
------------	--

10.2. Chemical stability

Stability	Stable under recommended storage conditions - see Section 7.
-----------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Stable under recommended storage conditions - see Section 7.
------------------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Avoid contact with oxidising agents, acids and bases.
--------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	Carbon monoxide (CO). Carbon dioxide (CO ₂). Nitrous gases (NO _x).
-------------------------------------	--

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Substance	Reaction product: bisphenol-A- (epichlorohydrin) epoxy resin (number average molecular weight <= 700)
Acute toxicity	<p>Effect tested: LD50 Route of exposure: Oral Value: > 15 000 mg/kg Animal test species: Rabbit</p> <p>Effect tested: LD50 Route of exposure: Dermal Value: 23 000 mg/kg Animal test species: Rabbit</p>
Substance	Bisphenol-F Epoxy resin
Acute toxicity	<p>Effect tested: LD50 Route of exposure: Oral Value: > 2000 mg/kg Animal test species: Rat</p> <p>Effect tested: LD50 Route of exposure: Dermal Value: > 2000 mg/kg Animal test species: Rabbit</p>
Substance	Oxirane, mono[(C12- 14- alkyloxy) methyl]derivs
Acute toxicity	<p>Effect tested: LD50 Route of exposure: Oral Value: > 5000 mg/kg Animal test species: Rat</p> <p>Effect tested: LD50 Route of exposure: Dermal Value: > 4500 mg/kg Animal test species: Rabbit</p>

Other information regarding health hazards

Toxicokinetics	Not known.
Inhalation	May be irritating to prolonged and repeated exposure.
Skin contact	The product may cause irritation by prolonged contact. The symptoms are redness, swelling, blistering and ulceration and usually develops slowly.
Eye contact	Irritating to eyes. Gives soreness and tearing.
Ingestion	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Sensitisation	Preparation contains an epoxy resin, which may cause sensitisation and development of allergy.
Mutagenicity	Not mutagenic.
Carcinogenicity, other information	No specific health warnings noted.
Reproductive toxicity	No specific health warnings noted.

Aspiration hazard, comments	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
-----------------------------	--

Symptoms of exposure

In case of ingestion	Severe irritation in nose and throat.
In case of skin contact	Risk of sensitisation or allergic reactions among sensitive individuals. Risk of sensitisation to epoxy and amines.
In case of inhalation	Vapours liberated during curing of the product may in high concentrations irritate the throat and respiratory system and cause coughing.
In case of eye contact	May irritate and cause redness and pain.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Reaction product: bisphenol-A- (epichlorohydrin) epoxy resin (number average molecular weight <= 700)
Aquatic toxicity, fish	Toxicity type: Acute Value: 2 mg/l Effect dose concentration: LC50 Exposure time: 96 hour(s) Species: Oncorhynchus mykiss
Substance	Bisphenol-F Epoxy resin
Aquatic toxicity, fish	Toxicity type: Acute Value: 2,54 mg/l Species: Leuciscus idus
Substance	Oxirane, mono[(C12- 14- alkyloxy) methyl]derivs
Aquatic toxicity, fish	Toxicity type: Acute Value: 1800 mg/l Effect dose concentration: LC50 Exposure time: 96 hour(s) Species: Oncorhynchus mykiss
Substance	Oxirane, mono[(C12- 14- alkyloxy) methyl]derivs
Aquatic toxicity, algae	Toxicity type: Acute Value: 844 mg/l Effect dose concentration: EC50 Exposure time: 72 hour(s)
Substance	Reaction product: bisphenol-A- (epichlorohydrin) epoxy resin (number average molecular weight <= 700)
Aquatic toxicity, crustacean	Toxicity type: Acute Value: 1,8 mg/l Effect dose concentration: EC50 Exposure time: 48 hour(s) Species: Daphnia magna
Substance	Bisphenol-F Epoxy resin

Aquatic toxicity, crustacean	Toxicity type: Acute Value: 2,55 mg/l Effect dose concentration: LC0 Exposure time: 48 hour(s) Species: Daphnia magna
Substance	Oxirane, mono[(C12- 14- alkyloxy) methyl]derivs
Toxicity to bacteria	Toxicity type: Acute Value: > 100 mg/l Effect dose concentration: EC50 Comments: activated sludge
Ecotoxicity	The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Persistence and degradability description/evaluation	This product does not contain any PBT or vPvB substances.
Biodegradability	Comments: No evidence for bioaccumulation potential.
Chemical oxygen demand (COD)	Comments: Not known.
Biological oxygen demand (BOD)	Comments: Not known.

12.3. Bioaccumulative potential

Bioconcentration factor (BCF)	Comments: Not known.
Bioaccumulation, comments	Not known.

12.4. Mobility in soil

Mobility	Not known.
Surface tension	Comments: Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This product does not contain any PBT or vPvB substances.
------------------------------------	---

12.6. Other adverse effects

Additional ecological information	Do not empty into drains or other waterways.
-----------------------------------	--

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate methods of disposal for the chemical	Do not allow runoffs! This chemical is toxic to organisms in water. See section 6 for further information.
EWC waste code	EWC waste code: 080409 waste adhesives and sealants containing organic solvents or other dangerous substances Classified as hazardous waste: Yes
EWL packing	EWC waste code: 150104 metallicpackaging

	Classified as hazardous waste: Yes
National regulations	Regulation 01.06 2004 nr. 930, on recycling of waste with subsequent amendments. Guidelines (Norsas) on collection and declaration of hazardous waste (2015).
NORSAS	7051

SECTION 14: Transport information

Dangerous goods	Yes
-----------------	-----

14.1. UN number

ADR/RID/ADN	3082
IMDG	3082
ICAO/IATA	3082

14.2. UN proper shipping name

Proper shipping name English ADR/RID/ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name/Danger releasing substance English ADR/RID/ADN	EPOXY RESIN
ADR/RID/ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name/danger releasing substance ADR/RID/ADN	EPOXY RESIN
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name/danger releasing substance IMDG	EPOXY RESIN
ICAO/IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name/danger releasing substance ICAO/IATA	EPOXY RESIN

14.3. Transport hazard class(es)

ADR/RID/ADN	9
Classification code ADR/RID/ADN	M6
IMDG	9
ICAO/IATA	9

14.4. Packing group

ADR/RID/ADN	III
IMDG	III
ICAO/IATA	III

14.5. Environmental hazards

IMDG Marine pollutant	Yes
-----------------------	-----

14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

Transport in bulk (yes/no)	No
----------------------------	----

Additional information

Hazard label ADR/RID/ADN	9
Hazard label IMDG	9
Hazard label ICAO/IATA	9

ADR/RID Other information

Tunnel restriction code	-
Limited quantity	LQ=5L
Transport category	3
Hazard No.	90
Other applicable information ADR/RID	90

IMDG Other information

EmS	F-A, S-F
-----	----------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

Assessed restrictions	By assessment no identified restrictions.
Restriction of chemicals according to Annex XVII (REACH)	No restrictions identified.
Other labelling requirements	No other labeling requirements.
Other label information	As a general rule, persons under 18 years of age are not allowed to work with this product. Users must be carefully instructed in the proper work procedure, the dangerous properties of the product and the necessary safety instructions. Contains epoxy constituents. See information supplied by the manufacturer.
EU occupational restrictions	No restrictions identified.
Biocides	No
Nanomaterial	No
References (laws/regulations)	EU Regulation No. 1907/2006 (REACH) Title IV, art. 31 and Annex II. EU Regulation on classification labeling and packaging of substances and preparations (abbreviated CLP) (EC) No 1272/2008 Annex XIV - List of substances subject to authorization. Substances that give great cause for concern. Annex XVII - Restrictions on the production, marketing and use of certain hazardous substances.

	Occupational exposure limits, guidance No 361 (2010) Avfallsforsl kriften, revised on 02/02/2009. ADR / RID 2019 Regulation No. 384 01 April 2009.
Declaration No.	311087

15.2. Chemical safety assessment

Chemical safety assessment performed	No
Exposure scenarios for mixture	No

SECTION 16: Other information

Supplier's notes	Information provided in the safety data sheet is prepared on the basis of information supplied by subcontractors, and according to information in our possession at the last entered revision date. The information is to be regarded as guidelines for safe use, processing, storage and transportation. It is assumed that the product is used in accordance with the description on the packaging or in the technical data sheet/product data sheet prepared by Hey'di AS. Any other use of the product, if necessary in combination with other products or processes are not recommended, unless otherwise agreed with Hey'di AS.
List of relevant H-phrases (Section 2 and 3)	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Last update date	19.06.2018
Version	1
Prepared by	Marit Taraldset
NOBB No.	10369189
URL for user guide	http://www.heydi.no
URL for brochure	http://www.heydi.no
URL for technical data	http://www.heydi.no