## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Nord	llux
-------------------------------------	------

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 47836101

_	•		
Typa	Λt	liaht	source:
IVDE	VI.	IIGIIL	source.

Lighting technology used:	LED	Non-directional or	NDLS	
		directional:		
Light source cap-type	LED Module			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light	No	
		source (CLS):		
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				

## Product parameters

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
- ·	nption in on- 00 h), rounded st integer	18	Energy efficiency class	E
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	2 100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	18,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	1 210	Spectral power dis-	See image
sions without	Width	32	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	45	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime-				
tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,458	
		nates (x and y)	0,410	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	11	Survival factor	1,00	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,86	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9	

(a)'-': not applicable; (b)'-': not applicable;

