Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 2015056101

Type	of	light	source:
-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		0	

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED Module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Product parameters

Product parameters							
Parameter		Value	Parameter	Value			
	General product parameters:						
<u> </u>	nption in on- 00 h), rounded st integer	15	Energy efficiency class	F			
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30004000			
On-mode power (P _{on}), expressed in W		14,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	23	Spectral power dis-	See image			
sions without	Width	294	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	294	range 250 nm to 800 nm, at full-load				

parts and non- lighting con- trol parts, if any (millime-					
tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,434		
		nates (x and y)	0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	11	Survival factor	0,90		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,1		

(a)'-': not applicable; (b)'-': not applicable;

