Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC35681

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

ing control

Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	constant cur-				
(or other electric interface)	rent: 200 mA				
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
	Product para	neters			
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on-	8	Energy efficiency	F		
mode (kWh/1000 h), rounded		class			
up to the nearest integer					
Useful luminous flux (фuse), in-	800 in	Correlated colour	3 000		

Useful luminous flux (фuse), in-	800 in	Correlated colour	
dicating if it refers to the flux in	Sphere (360°)	temperature,	
a sphere (360º), in a wide cone		rounded to the near-	
(120°) or in a narrow cone (90°)		est 100 K, or the	

(120º) or in a narrow cone (90º)			est 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	
On-mode power (P _{on}), expressed in W		8,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		0,00	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	206	Spectral power dis-	See image
sions without	Width	93	tribution in the	in last page
separate con- trol gear, light-		1	range 250 nm to 800 nm. at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,434		
		nates (x and y)	0,403		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

