## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 84181001

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED Module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

## **Product parameters**

Froduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
_ ·	mption in on- 00 h), rounded st integer	9	Energy efficiency class	E		
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	983 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	8,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	100	Spectral power dis-	See image		
sions without	Width	40	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	190	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,437 0,398			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)'-': not applicable; (b)'-': not applicable;

