## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 46951003

I V DC OI IISIIL JOUI CC	Type	of lig	tht s	ource:
--------------------------	------	--------	-------	--------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED Module		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product para	ameters	

Parameter		Value	Parameter	Value
General product parameters:				
٠,	nption in on- 00 h), rounded st integer	10	Energy efficiency class	F
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	622 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	9,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without	Height	150	Spectral power distribution in the	See image
	Width	60		in last page
separate con- trol gear, light- ing control	Depth	150	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,437 0,398
Parameters for LED and OLED lig	tht sources:		
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,96		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)'-': not applicable; (b)'-': not applicable;

