## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 47520101

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	<b>3</b> Uui C	c.

Lighting technology used:	LED	Non-directional or	NDLS	
		directional:		
Light source cap-type	LED MODUL			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light	No	
		source (CLS):		
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				

Froduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consun mode (kWh/100 up to the neares	00 h), rounded	1	Energy efficiency class	F		
Useful luminous dicating if it refe a sphere (360°), (120°) or in a na	ers to the flux in , in a wide cone	350 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P <sub>on</sub> ), expressed in W		0,4	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	38	Spectral power dis-	See image		
sions without	Width	82	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	82	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime-					
tre)		If was assistations			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,458		
		nates (x and y)	0,410		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,90		
the lumen maintenance factor	0,96				
Parameters for LED and OLED m	ains light sources:				
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,1		

(a)'-': not applicable; (b)'-': not applicable;

