Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: O | SRAM |
|----------------------------------|------|
|----------------------------------|------|

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC34199

| T | - 6 | 10 - 1- 1 | | |
|----------|------------|-----------|---------|---|
| IVna | α T | IIσnt | source: | , |
| IVDC | vı | HEILL | Jourte. | |

| Lighting technology used: | CFLni | Non-directional or directional: | NDLS |
|-------------------------------|--------|---------------------------------|------|
| Light source cap-type | G24d-1 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |
| Product parameters | | | |

| Parameter | | Value | Parameter | Value |
|---|--|-------------------------|--|--------------|
| | General product parameters: | | | |
| ٠, | nption in on- 00 h), rounded st integer | 11 | Energy efficiency class | G |
| dicating if it refe a sphere (360°) | s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º) | 600 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 10,7 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| (P _{net}) for CLS, 6 | candby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |
| Outer dimen- | Height | 109 | Spectral power distribution in the | See image |
| sions without | Width | 12 | | in last page |
| separate con- trol gear, light- ing control | Depth | 12 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | |
|--|---|------------------------------------|----------------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,455 0,415 |

(a)'-': not applicable; (b)'-': not applicable;

