Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LEDVANCE
Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier:	AC33911
-------------------	---------

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Duodust novementors			
Anti-glare shield:	No	Dimmable:	Yes
High luminance light source:	No		
Colour-tuneable light source:	Yes	Envelope:	-
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
(or other electric interface)			
Light source cap-type	E27		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Product parameters

Froduct parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
Energy consummode (kWh/10 up to the neares	00 h), rounded	9	Energy efficiency class	F	
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500	
On-mode pow pressed in W	ver (P _{on}), ex-	9,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	111	Spectral power dis-	See image	
sions without	Width	60	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60
		Chromaticity coordinates (x and y)	0,463 0,420
Parameters for LED and OLED light sources:			
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,70		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)'-': not applicable; (b)'-': not applicable;

