


300L rubber cable lightchain

Product information sheet

Supplier's name or trade mark:			
Supplier's address:			
Model identifier:	9060569		
Type of light source:	LED Light		
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	other electric interface		
Mains or non-mains:	NMLS	Connected light source (CLS):	no
Colour-tuneable light source:	no	Envelope:	no
High luminance light source:	no		
Anti-glare shield:	no	Dimmable:	no

Product parameters

General product parameters:

Energy consumption in on-mode (kWh/1000h)	6		Energy efficiency class	G	
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	500		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures	2500	
	sphere				
On-mode power (P_{on}), expressed in W	5,8		Standby power (P_{sb}), expressed in W	0,00	
Networked standby power (P_{net}) for CLS, expressed in W	0,00		Colour rendering index	88,4	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	29900	Spectral power distribution in the range 250 nm to 800 nm, at full-load		
	Width	30			
	Depth	8			
Claim of equivalent power	-		If yes, equivalent power (W)	-	
			Chromaticity coordinates	x	0,485

		(x and y)	y	0,427
--	--	-----------	---	-------

Parameters for directional light sources:			
Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles	
Parameters for LED and OLED light sources:			
R9 colour rendering index value	>0	Survival factor	0,9
the lumen maintenance factor	0,9		
Parameters for LED and OLED for mains light sources			
displacement factor (cos ϕ_1)	0,00	Colour consistency in McAdam ellipses	3,8
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0