## 300L warm white LED lightchain

Product information sheet							
Supplier's name or trade mark:							
Supplier's address:							
Model identifier:	<mark>9060578</mark>						
Type of light source:	LED Light						
Lighting technology used:	LED		Non-directional or directional:	NDLS			
Light source cap-type (or other electric interface)	other electric interface						
Mains or non-mains:	NMLS		Connected light source (CLS):	no			
Colour-tuneable light source:	no		Envelope:	no			
High luminance light source:	no						
Anti-glare shield:	no		Dimmable:	no			
Product parameters							
General product parameters:							
Energy consumption in on-mode (kWh/1000h)	4		Energy efficiency class	G			
Useful luminous flux (Φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	350 changed to 320 sphere		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures	2700			
On-mode power (Pon), expressed in W	3,6		Standby power (Psb), expressed in W	0,00			
Networked standby power (Pnet) for CLS, expressed in W	0,00		Colour rendering index	88,1			
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height Width Depth	29900 27 5	Spectral power distributio in the range 250 nm to 800 nm, at full-load				
Claim of equivalent power	-		If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	x 0,463			
				y 0,420			

Parameters for directional light sources:						
Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	>0	Survival factor	0,9			
the lumen maintenance factor	0,9					
Parameters for LED and OLED for ma	ins light sources					
displacement factor ( $\cos \varphi 1$ )	0,00	Colour consistency in McAdam ellipses	3,7			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)				
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			