2D-96L tree

Product information sheet								
Supplier's name or trade mark:								
Supplier's address:								
Model identifier:	9060590							
Type of light source:	LED Light							
Lighting technology used:	LEI	D	Non-directional or directional:	NDLS				
Light source cap-type (or other electric interface)	other electri	c interface						
Mains or non-mains:	NMLS		Connected light source (CLS):	no				
Colour-tuneable light source:	no		Envelope:	no				
High luminance light source:	no							
Anti-glare shield:	no		Dimmable:	no				
Product parameters								
General product parameters:								
Energy consumption in on-mode (kWh/1000h)	4		Energy efficiency class	G				
Useful luminous flux (Фuse),	120 sphere		Correlated colour temperature, rounded to					
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)			the nearest 100 K, or the range of correlated colour temperatures		2900			
On-mode power (Pon), expressed in W	3.6		Standby power (Psb), expressed in W	0,00				
Networked standby power (Pnet) for CLS, expressed in W	0,00		Colour rendering index	89,2	89,2			
Outer dimensions without	Height 1500 Width 600 Depth 27		Spectral power distribution		1.0 = 2.14441000000 1.0 = 2.144410000000 1.0 = 2.14441000000000000000000000000000000000			
separate control gear, lighting control parts and non-lighting			in the range 250 nm to	0.0 0.0				
control parts, if any (millimetre)			800 nm, at full-load	0.7 to all position of the table				
Claim of equivalent power	-		If yes, equivalent power (W)	-	-			
			Chromaticity coordinates	х	0,454			
			(x and y)	у	0,412			

Parameters for directional light sources:						
Peak luminous intensity (cd)		Beam angle in degrees, or the				
Peak luminous intensity (cd)		range of beam angles				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	>0	Survival factor	0,9			
the lumen maintenance factor	0,9					
Parameters for LED and OLED for mains light sources						
displacement factor (cos φ1)	0,00	Colour consistency in	4,9			
displacement factor (cos ψ1)		McAdam ellipses	7,0			
Claims that an LED light source replaces a		If you then replacement				
fluorescent light source without integrated	-	If yes then replacement				
ballast of a particular wattage.		claim (W)				
First and the (Battan)	0,0	Stroboscopic effect metric	0,0			
Flicker metric (Pst LM)		(SVM)				