Product information sheet

Supplier's name or trade mark:			
Supplier's address:			
Model identifier:	9060596		
Type of light source:	LED Light		
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	other electric interface		
Mains or non-mains:	NMLS	Connected light source (CLS):	no
Colour-tuneable light source:	no	Envelope:	no
High luminance light source:	no		
Anti-glare shield:	no	Dimmable:	no

Product parameters

General product parameters:

Energy consumption in on-mode (kWh/1000h)	4		Energy efficiency class	G
Useful luminous flux (Φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	280 sphere		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures	2800
On-mode power (Pon), expressed in W	3,6		Standby power (Psb), expressed in W	0,00
Networked standby power (Pnet) for CLS, expressed in W	0,00		Colour rendering index	89,4
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	1100	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
	Width	720		
	Depth	720		
Claim of equivalent power	-		If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	x: 0,454 y: 0,412

Parameters for directional light sources:

Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles	
Parameters for LED and OLED light sources:			
R9 colour rendering index value	>0	Survival factor	0,9
the lumen maintenance factor	0,9		
Parameters for LED and OLED for mains light sources			
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	3,3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0