## 2m-400L branch tree

Product information sheet								
Supplier's name or trade mark:								
Supplier's address:								
Model identifier:	9060597							
Type of light source:	LED Light							
Lighting technology used:	LED		Non-directional or directional:	NDLS				
Light source cap-type (or other electric interface)	other electric interface							
Mains or non-mains:	NMLS		Connected light source (CLS):	no				
Colour-tuneable light source:	no		Envelope:	no				
High luminance light source:	no							
Anti-glare shield:	no		Dimmable:	no				
	Produ	ıct para	ımeters					
General product parameters:								
Energy consumption in on-mode (kWh/1000h)	6		Energy efficiency class	F				
Useful luminous flux (Фuse),	flux (Фuse), 560		Correlated colour temperature, rounded to	2700				
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	sphere		the nearest 100 K, or the range of correlated colour temperatures					
On-mode power (Pon), expressed in W	6		Standby power (Psb), expressed in W	0,00				
Networked standby power (Pnet) for CLS, expressed in W	0,00		Colour rendering index	80				
Outer dimensions without	Height 2000		Spectral power distribution	1.0 = 5.1266-003887/as				
separate control gear, lighting control parts and non-lighting	Width	1000	in the range 250 nm to	1.0				
control parts, if any (millimetre)	Depth	<mark>1000</mark>	800 nm, at full-load	0.3 10 10 10 10 10 10 10 10 10 10 10 10 10				
Claim of equivalent power	-		If yes, equivalent power (W)	-				
			Chromaticity coordinates	x 0,463				

(	(x and y)	у	0,420

Parameters for directional light sources:							
Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles					
Parameters for LED and OLED light sources:							
R9 colour rendering index value	>0	Survival factor	0,9				
the lumen maintenance factor	0,9						
Parameters for LED and OLED for mains light sources							
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	5				
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)					
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0				