



## 1500L snake light


### Product information sheet

Supplier's name or trade mark:			
Supplier's address:			
Model identifier:	9060604		
Type of light source:	LED Light		
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	other electric interface		
Mains or non-mains:	NMLS	Connected light source (CLS):	no
Colour-tuneable light source:	no	Envelope:	no
High luminance light source:	no		
Anti-glare shield:	no	Dimmable:	no

### Product parameters

#### General product parameters:

Energy consumption in on-mode (kWh/1000h)	5	Energy efficiency class	G
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1100 changed to 430	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures	3000
	sphere		
On-mode power ( $P_{on}$ ), expressed in W	4,8	Standby power ( $P_{sb}$ ), expressed in W	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W	0,00	Colour rendering index	87,5
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	30000	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	27	
	Depth	5	
Claim of equivalent power	-	If yes, equivalent power (W)	-
		Chromaticity coordinates	x 0,437



		(x and y)	y	0,405
--	--	-----------	---	-------

<b>Parameters for directional light sources:</b>			
--	--	--	--

Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles	
------------------------------	--	--	--

<b>Parameters for LED and OLED light sources:</b>			
---	--	--	--

R9 colour rendering index value	>0	Survival factor	0,9
---------------------------------	----	-----------------	-----

the lumen maintenance factor	0,9		
------------------------------	-----	--	--

<b>Parameters for LED and OLED for mains light sources</b>			
--	--	--	--

displacement factor (cos $\phi_1$ )	0,00	Colour consistency in McAdam ellipses	5,3
-------------------------------------	------	---------------------------------------	-----

Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)	
---	---	-----------------------------------	--

Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0
-------------------------	-----	----------------------------------	-----