

1.5m-240L branch tree


Product information sheet

Supplier's name or trade mark:			
Supplier's address:			
Model identifier:	9060610		
Type of light source:	LED Light		
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	other electric interface		
Mains or non-mains:	NMLS	Connected light source (CLS):	no
Colour-tuneable light source:	no	Envelope:	no
High luminance light source:	no		
Anti-glare shield:	no	Dimmable:	no

Product parameters

General product parameters:

Energy consumption in on-mode (kWh/1000h)	4	Energy efficiency class	G
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	280	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures	2700
	sphere		
On-mode power (P_{on}), expressed in W	3,6	Standby power (P_{sb}), expressed in W	0,00
Networked standby power (P_{net}) for CLS, expressed in W	0,00	Colour rendering index	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	1500	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	800	
	Depth	800	
Claim of equivalent power	-	If yes, equivalent power (W)	-
		Chromaticity coordinates	x 0,463



		(x and y)	y	0,420
--	--	-----------	---	-------

Parameters for directional light sources:

Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles	
------------------------------	--	--	--

Parameters for LED and OLED light sources:

R9 colour rendering index value	>0	Survival factor	0,9
the lumen maintenance factor	0,9		

Parameters for LED and OLED for mains light sources

displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0